




CONFIDENTIAL

TABLE 1.1, ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	-40 to +85 degrees C
Storage Temperature Range	-55 to +125 degrees C
Vcc Voltage, Vdc	+5.2
Vtune Voltage, Vdc	+5.0
DC Voltage applied to RF out	+/- 25



ALL DIMENSIONS IN INCHES

TABLE 1.2, CONTACT ASSIGNMENTS

CONTACT ASSIGNMENTS:	
1: RF OUT	
2: SUPPLY INPUT	
3: TUNING VOLTAGE INPUT	
ALL OTHER CONTACTS ARE GROUND	

Unless otherwise specified, dimensions are in inches
 TOLERANCES
 .X = +/- .1
 .XX = +/- .01
 .XXX = +/- .005
 ANG = +/- 2°
 Universal Microwave Corporation
 Proprietary Information
 Prepared by: A.BYRD 10/18/05
 Engineer:
 Universal Microwave Corporation
 2339 Destiny Way
 Odessa, FL 33556

Universal Microwave Corp.

SPECIFICATION CONTROL
 DRAWING FOR UMZ-1151-R16-G

SIZE A	FSCM NO.	DWG NO. UP-1151	REV A
SCALE N/A		SHEET 1 OF 2	

	MIN.	TYP.	MAX.
Frequency, MHz	450		470
Power Output, dBm	-2.0	0	+2.0
Harmonics, dBc		-15	-12
SSB Phase Noise, dBc/Hz:			
@ Offset = 1kHz		-95	-90
@ Offset = 10kHz		-120	-115
@ Offset = 100kHz		-140	-135
@ Offset = 1MHz		-160	-155
@ Offset = 10MHz			
Pushing, MHz/V		.1	.2
Pulling, MHz p-p, @12dBr, all phases		.2	.3
Tuning Voltage, Vdc	+0.5		+4.5
Tuning Sensitivity, MHz/V	6.0	8.0	10.0
Frequency drift with temperature:			
@ -40°C, MHz		1.0	2.0
@ +85°C, MHz		1.0	2.0
Supply Voltage, Vdc	+4.5	+4.7	+4.9
Supply Current, mA		15	20
Output Power @ $V_t = 0$ and 5V	-2.0		
Tuning Port Capacitance, pF		100	
3dB Modulation Bandwidth, kHz		1000	

TABLE 1.3 ELECTRICAL SPECIFICATIONS

SPECIFICATION CONTROL DRAWING			
Drawing No. UMZ-1151-R16-G			
Size	A	REV	A
Engineer:	PJE 10/18/05	SHEET 2 OF 2	