




CONFIDENTIAL

TABLE 1.1, ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	-40 to +85 degrees C
Storage Temperature Range	-55 to +125 degrees C
Vcc Voltage, Vdc	+5.25
Vtune Voltage, Vdc	+5.0
DC Voltage applied to RF out	+/- 25



ALL DIMENSIONS IN INCHES

TABLE 1.2, CONTACT ASSIGNMENTS

CONTACT ASSIGNMENTS:	
1: RF OUT	
2: SUPPLY INPUT	
3: TUNING VOLTAGE INPUT	
ALL OTHER CONTACTS ARE GROUND	

Unless otherwise specified, dimensions are in inches
 TOLERANCES
 .X =+/- .1
 .XX =+/- .01
 .XXX =+/- .005
 ANG =+/- 2°
 Universal Microwave Corporation
 Proprietary Information
 Prepared by: A.BYRD 9/15/05
 Engineer:
 Universal Microwave Corporation
 2339 Destiny Way
 Odessa, FL 33556

Universal Microwave Corp.

SPECIFICATION CONTROL
 DRAWING FOR UMZ-1188-R16

SIZE A	FSCM NO.	DWG NO. UP-1188	REV A
SCALE N/A		SHEET 1 OF 2	

	MIN.	TYP.	MAX.
Frequency, MHz	160		180
Power Output, dBm	+1.0	+3.0	+5.0
Harmonics, dBc		-25	-15
SSB Phase Noise, dBc/Hz:			
@ Offset = 1kHz		-78	-73
@ Offset = 10kHz		-103	-98
@ Offset = 100kHz		-123	-118
@ Offset = 1MHz		-143	-138
Pushing, MHz/V		0.5	1
Pulling, MHz p-p, @12dB_r, all phases		0.5	1
Tuning Voltage, Vdc	+0.5		+4.5
Tuning Sensitivity, MHz/V		12	
Frequency drift with temperature:			
@ -40°C, MHz		2.0	
@ +85°C, MHz		2.0	
Supply Voltage, Vdc	+4.5	+4.75	+5.0
Supply Current, mA		8	10
Output Power @ V_t = 0 and 5V	+1.0		
Tuning Port Capacitance, pF		330	
3dB Modulation Bandwidth, kHz		100	

TABLE 1.3 ELECTRICAL SPECIFICATIONS

SPECIFICATION CONTROL DRAWING			
Drawing No. UMZ-1188-R16			
Size	A	REV	A
Engineer:	PJE 9/15/05	SHEET 2 OF 2	