




CONFIDENTIAL

TABLE 1.1, ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	-40 to +85 degrees C
Storage Temperature Range	-55 to +125 degrees C
Vcc Voltage, Vdc	+5.5
Vtune Voltage, Vdc	+5.0
DC Voltage applied to RF out	+/- 0V



ALL DIMENSIONS IN INCHES

TABLE 1.2, CONTACT ASSIGNMENTS

CONTACT ASSIGNMENTS:	
1: RF OUT	
2: SUPPLY INPUT	
3: TUNING VOLTAGE INPUT	
ALL OTHER CONTACTS ARE GROUND	

Unless otherwise specified, dimensions are in inches
 TOLERANCES
 .X =+/- .1
 .XX =+/- .01
 .XXX =+/- .005
 ANG =+/- 2°
 Universal Microwave Corporation
 Proprietary Information
 Prepared by: A.BYRD 3/21/06
 Engineer:
 Universal Microwave Corporation
 2339 Destiny Way
 Odessa, FL 33556

Universal Microwave Corp.

SPECIFICATION CONTROL
 DRAWING FOR UMZ-144-A16

SIZE A	FSCM NO.	DWG NO. UP-144	REV B
SCALE N/A		SHEET 1 OF 2	

	MIN.	TYP.	MAX.
Frequency, MHz	376		410
Power Output, dBm	+1.0	+3.0	+5.0
Harmonics, dBc		-15	-10
SSB Phase Noise, dBc/Hz:			
@ Offset = 1kHz		-93	-88
@ Offset = 10kHz		-118	-113
@ Offset = 100kHz		-138	-133
@ Offset = 1MHz		-158	-153
@ Offset = 10MHz		-160	-153
Pushing, MHz/V		1	2
Pulling, MHz p-p, @12dB _r , all phases		1	5
Tuning Voltage, Vdc	+0.5		+4.5
Tuning Sensitivity, MHz/V		13	
Frequency drift with temperature:			
@ -40°C, MHz		1	3
@ +85°C, MHz		1	3
Supply Voltage, Vdc		+5.0	
Supply Current, mA		15	
Output Power @ $V_t = 0$ and 5V	0		
Tuning Port Capacitance, pF		100	
3dB Modulation Bandwidth, kHz		100	

TABLE 1.3 ELECTRICAL SPECIFICATIONS

SPECIFICATION CONTROL DRAWING			
Drawing No. UMZ-144-A16			
Size	A		REV B
Engineer:	PJE 3/21/06		SHEET 2 OF 2