




CONFIDENTIAL

TABLE 1.1, ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	-40 to +85 degrees C
Storage Temperature Range	-55 to +125 degrees C
Vcc Voltage, Vdc	+5.5
Vtune Voltage, Vdc	+5.0
DC Voltage applied to RF out	+/- 25



ALL DIMENSIONS IN INCHES

TABLE 1.2, CONTACT ASSIGNMENTS

CONTACT ASSIGNMENTS:	
1: RF OUT	
2: SUPPLY INPUT	
3: TUNING VOLTAGE INPUT	
ALL OTHER CONTACTS ARE GROUND	

Unless otherwise specified, dimensions are in inches
 TOLERANCES
 .X = +/- .1
 .XX = +/- .01
 .XXX = +/- .005
 ANG = +/- 2°
 Universal Microwave Corporation
 Proprietary Information
 Prepared by: A.BYRD 8/17/05
 Engineer:
 Universal Microwave Corporation
 2339 Destiny Way
 Odessa, FL 33556

Universal Microwave Corp.

SPECIFICATION CONTROL
 DRAWING FOR UMV-2550-R16-G

SIZE A	FSCM NO.	DWG NO. UP-774	REV B
SCALE N/A		SHEET 1 OF 2	

	MIN.	TYP.	MAX.
Frequency, MHz	2500		2600
Power Output, dBm	-2.5	0	+2.5
Harmonics, dBc		-15	-10
SSB Phase Noise, dBc/Hz:			
@ Offset = 1kHz		-79	-74
@ Offset = 10kHz		-104	-99
@ Offset = 100kHz		-124	-119
@ Offset = 1MHz		-144	-139
@ Offset = 10MHz		-164	-159
Pushing, MHz/V		0.5	1.0
Pulling, MHz p-p, @12dB _r , all phases		2.0	3.0
Tuning Voltage, Vdc	+0.5		+4.5
Tuning Sensitivity, MHz/V		36	
Frequency drift with temperature:			
@ -40°C, MHz		5	8
@ +85°C, MHz		5	8
Supply Voltage, Vdc		+5.0	
Supply Current, mA		27	
Output Power @ $V_t = 0$ and 5V	-2.5		
Tuning Port Capacitance, pF		20	
3dB Modulation Bandwidth, kHz		1000	

TABLE 1.3 ELECTRICAL SPECIFICATIONS

SPECIFICATION CONTROL DRAWING			
Drawing No. UMV-2550-R16-G			
Size	A	REV	B
Engineer: PJE 8/17/05		SHEET 2 OF 2	