


CONFIDENTIAL

TABLE 1.1, ABSOLUTE MAXIMUM RATINGS

Operating Temperature Range	-40 to +85 degrees C
Storage Temperature Range	-55 to +125 degrees C
Vcc Voltage, Vdc	+5.5
Vtune Voltage, Vdc	+5.0
DC Voltage applied to RF out	+/- 25



ALL DIMENSIONS IN INCHES

TABLE 1.2, CONTACT ASSIGNMENTS

CONTACT ASSIGNMENTS:	
1: RF OUT	
2: SUPPLY INPUT	
3: TUNING VOLTAGE INPUT	
ALL OTHER CONTACTS ARE GROUND	

Unless otherwise specified,
dimensions are in inches

Universal Microwave Corporation
Proprietary Document

Prepared by: M.Banks 1/20/04
Engineer:

Universal Microwave Corporation
2339 Destiny Way
Dadea, FL 33556

Universal Microwave Corp.

SPECIFICATION CONTROL DRAWING FOR UMV-2350-R16

SIZE
A

FSCM NO.

DWG NO.

UP-772

REV
A

SCALE: N/A

SHEET 1 OF 2

	MIN.	TYP.	MAX.
Frequency, MHz	2300		2400
Power Output, dBm	-2.5	0	+2.5
Harmonics, dBc	--	-20	-10
SSB Phase Noise, dBc/Hz			
@ Offset = 1kHz	--	-80	-75
@ Offset = 10kHz	--	-106	-101
@ Offset = 100kHz	--	-126	-121
@ Offset = 1MHz	--	-146	-141
@ Offset = 10MHz	--	-159	-154
Pushing, MHz/V	--	0.5	1
Pulling, MHz p-p, @12dBr, all phases	--	1	2
Tuning Voltage, Vdc	+0.5		+4.5
Tuning Sensitivity, MHz/V	--	36	--
Frequency drift with temperature			
@ -40 degrees C, MHz	--	7	11
@ +85 degrees C, MHz	--	7	11
Supply Voltage, Vdc	--	+5.0	--
Supply Current, mA _{dc}	--	25	30
Output Power @ V _{tune} = 0 and 4.5V	-3.0	--	--
Tuning Port Capacitance, pF	--	47	--
3dB Modulation Bandwidth, kHz	--	1000	--

TABLE 1.0, ELECTRICAL SPECIFICATIONS

Unless otherwise specified, dimensions are in inches Universal Microwave Corporation Proprietary Document	Universal Microwave Corp. SPECIFICATION CONTROL DRAWING FOR UMV-2350-R16			
	Prepared by: M.BANKS 1/20/04	SIZE A	FSCM NO.	DWG NO. UP-772
Universal Microwave Corporation 2339 Destiny Way Odessa, FL 33556	SCALE: N/A		SHEET 1 OF 2	